NSN 4820-00-836-1344

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-836-1344 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Valve stem lock shield and pressure tight outlet side **Maximum Operating Pressure:** 10500.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 5000.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches all ends Material: Stainless steel Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life:

N/a **Unit Of Measure:**

NSN 4820-00-836-1344

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0