## NSN 4820-00-836-1853

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-836-1853

| Pipe Size Accommodated:                                       |
|---|
| 0.500 inches 1st end  |
| Flow Control Device:  |
| Poppet  |
| Disk Loading Method:  |
| Spring  |
| Maximum Operating Temp:                                       |
| 150.0 degrees fahrenheit single response                      |
| Connection Style:   |
| Streamlined with one brazing ring err-100                     |
| Valve Operation Method:                                       |
| Automatic   |
| Connection Type:  |
| Unthreaded internal pipe 1st end                              |
| Adjustable Pressure Range:                                    |
| +35.0/+44.0 pounds per square inch                            |
| Maximum Operating Pressure:                                   |
| 400.0 pounds per square inch single response                  |
| Material:   |
| Nickel alloy seat   |
| Media For Which Designed:                                     |
| Water, salt single response                                   |
| Style Designator:   |
| Err-090   |
| Reference Number Differentiating Characteristics:             |
| As differentiated by type a2 class c on the mfg dwg e8529j64m |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A046b0  |
|   |
|   |