

View Online at <https://aerobasegroup.com/nsn/4820-00-836-7563>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flareless all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.500 inches all ends

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

0.750 inches 1st end

Special Features:

175.0 psi valve cracking pressure

Material:

Steel comp 440a flow control device

Material Specification:

Qq-s-763, class 440a federal specification single material response body

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.