## NSN 4820-00-837-3144



Safety Relief Valve - Page 1 of 2	Grou
View Online at https://aerobasegroup.com/nsn/4820-00-837-3144	
Pipe Size Accommodated:	
1.500 inches all ends	
Thread Direction:	
Right-hand all ends	
Flow Control Device:	
Poppet	
Bonnet Type:	
Inside spring	
Bonnet Attachment Method:	
Threaded	
Disk Loading Method:	
Spring	
Valve Discharge Flow Rate:	
398.0 gallons per minute	
Maximum Operating Temp:	
200.0 degrees fahrenheit 2nd response	
Connection Style:	
G9 plain, optional en (pipe) all ends	
Valve Operation Method:	
Automatic	
Connection Type:	
Threaded internal pipe all ends	
Features Provided:	
Bonnet packing and pressure tight outlet side	
Thready Qty Per Inch (tpi):	
11-1/2 all ends	
Adjustable Pressure Range:	
+801.0/+2000.0 pounds per square inch	
Maximum Operating Pressure:	
4000.0 pounds per square inch 2nd response	
Thread Size:	
1.500 inches all ends	
Material:	
Steel stem	
Media For Which Designed:	

Oil 1st response

Style Designator:

Err-090

**Thread Series Designator:** 

Npt all ends

**Reference Number Differentiating Characteristics:** 

As differentiated by size of valve

## NSN 4820-00-837-3144

Safety Relief Valve - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0