NSN 4820-00-838-6406

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-838-6406

| Pipe Size Accommodated: |
|---|
| 3.000 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Union |
| Renewable Seat Ring Type: |
| Pressed-in |
| Maximum Operating Temp: |
| 550.0 degrees fahrenheit single response |
| Connection Style: |
| G9 plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Bonnet packing |
| Thready Qty Per Inch (tpi): |
| 8 1st end |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch 2nd response |
| Thread Size: |
| 3.000 inches 1st end |
| Material: |
| Copper alloy body |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt 1st end |
| Reference Number Differentiating Characteristics: |
| As differentiated by valve size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-838-6406

Globe Valve - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A046b0