

View Online at <https://aerobasegroup.com/nsn/4820-00-840-0944>

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube all ends

Mounting Position:

Horizontal

Thready Qty Per Inch (tpi):

16 all ends

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees all ends

Outside Diameter Tube Accommodated:

0.500 inches all ends

Material:

Stainless steel flow control device

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Test Data Document:

99240-2c6408 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0