NSN 4820-00-840-6032

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-840-6032

0.250 inches all ends						
Thread Direction:						
Right-hand all ends						
Flow Control Device:						
Diaphragm						
Bonnet Type:						
Inside spring						
Bonnet Attachment Method:						
Bolted						
Disk Loading Method:						
Spring						
Renewable Seat Ring Type:						
Welded						
Maximum Operating Temp:						
200.0 degrees fahrenheit single response						
Connection Style:						
G9 plain, optional en (pipe) all ends						
Valve Operation Method:						
Automatic						
Connection Type:						
Threaded internal pipe all ends						
Features Provided:						
Bonnet packing and pressure tight outlet side						
Adjustable Pressure Range:						
+45.0/+115.0 pounds per square inch						
Maximum Operating Pressure:						
115.0 pounds per square inch single response						
Thread Size:						
0.250 inches all ends						
Special Features:						
W/handwheel for setting pressure						
Material:						
Steel stem						
Media For Which Designed:						
Hydraulic fluid, mineral base 3rd response						
Style Designator:						
Err-090						
Thread Series Designator:						
Npt all ends						
Shelf Life:						
N/a						

NSN 4820-00-840-6032

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0