## NSN 4820-00-840-6032

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-840-6032

Pipe Size Accommodated: 0.250 inches all ends **Thread Direction:** Right-hand all ends Flow Control Device: Diaphragm **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Bolted **Disk Loading Method:** Spring **Renewable Seat Ring Type:** Welded Maximum Operating Temp: 200.0 degrees fahrenheit single response **Connection Style:** 

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

**Connection Type:** 

Threaded internal pipe all ends

**Features Provided:** 

Bonnet packing and pressure tight outlet side

Adjustable Pressure Range:

+45.0/+115.0 pounds per square inch

### Maximum Operating Pressure:

115.0 pounds per square inch single response

### **Thread Size:**

0.250 inches all ends

#### **Special Features:**

W/handwheel for setting pressure

Material:

Steel stem

Media For Which Designed:

Hydraulic fluid, mineral base 3rd response

**Style Designator:** 

Err-090

**Thread Series Designator:** 

Npt all ends

Shelf Life:

N/a

# NSN 4820-00-840-6032

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

