## NSN 4820-00-840-6282

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-840-6282

| Flow Control Device:  |
|---|
| Disk  |
| Bonnet Type:  |
| Outside screw-yoke  |
| Bonnet Attachment Method:   |
| Bolted  |
| Bolt Hole Quantity:   |
| 4 all ends  |
| Valve Operation Method:   |
| Manual  |
| Flange Shape:   |
| Round with holes all ends   |
| Connection Type:  |
| Flange all ends   |
| Valve Size:   |
| 1.000 inches  |
| Maximum Operating Pressure:   |
| 300.0 pounds per square inch single response  |
| Outside Diameter:   |
| 4.875 inches all ends   |
| Face To Face Distance:  |
| 8.000 inches  |
| Thickness:  |
| 0.688 inches all ends   |
| Bolt Hole Diameter:   |
| 0.750 inches all ends   |
| Bolt Circle Diameter:   |
| 3.500 inches all ends   |
| Flange Face Design:   |
| Raised straight all ends  |
| Raised Face Height:   |
| 0.062 inches all ends   |
| Raised Face Diameter:   |
| 2.000 inches all ends   |
| Special Features:   |
| Valves are avaiable in stainless steels and nickel alloys; end flanges iaw ansi b16.5 |
| Material:   |
| Stainless steel flow control device   |
| Material Specification:   |
| Astm a276, type 316 assn standard single material response stem                       |
| Style Designator:   |
| Err_000   |

Err-090

## NSN 4820-00-840-6282

Globe Valve - Page 2 of 2



| Furnished Items And Q | ≀uantity: |
|-----------------------|-----------|
|-----------------------|-----------|

1 handwheel

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0