## NSN 4820-00-840-6283

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-840-6283

Flow Control Povices
Flow Control Device:
Disk T.
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted  Bott Hale Counties
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Manual Shares Shares
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
3.750 inches all ends
Face To Face Distance:
6.000 inches
Thickness:
0.500 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
2.625 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.081 inches all ends
Raised Face Diameter:
1.383 inches all ends
Special Features:
Special discs are available on special order; end flanges iaw ansi b16.5, face to face dimensions iaw ansi b16.10
Material:
Steel uns j92900 body
Material Specification:
Astm a-351, grade cf8m assn standard single material response body
Style Designator:

Err-090

## NSN 4820-00-840-6283

Globe Valve - Page 2 of 2



Furnished	Items	And	Quantity:
-----------	-------	-----	-----------

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0