

View Online at <https://aerobasegroup.com/nsn/4820-00-840-6283>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

0.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

3.750 inches all ends

Face To Face Distance:

6.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

2.625 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.081 inches all ends

Raised Face Diameter:

1.383 inches all ends

Special Features:

Special discs are available on special order; end flanges iaw ansi b16.5, face to face dimensions iaw ansi b16.10

Material:

Steel uns j92900 body

Material Specification:

Astm a-351, grade cf8m assn standard single material response body

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0