## NSN 4820-00-842-2926

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-842-2926

Rody	/ Mate	rial:
DOUV	, iviate	#IIaI.

Aluminum alloy, qq-a-367, comp 2014, t6

**Outside Surface Treatment:** 

Anodized, mil-a-8625, type 2

**Body Style:** 

Tee angle

Media For Which Designed:

Hydraulic fluid, petroleum base

**First End Connection Type:** 

Threaded internal boss

First End Style Designator:

Gasket seal

First End Thread Size And Series/type Designator:

7/16-20 unif

First End Thread Class:

3b

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Third End Relationship With Preceding Ends:

Identical with first end

**Seat Material:** 

Cres qq-s-763 class 440c fscm 81348

**Center To Center Distance:** 

1.000 inches

**Packing Material:** 

Synthetic rubber mil-p-25732 fscm 81349

Flow Control Device:

Ball, ported

Flow Control Device Material:

Cres qq-s-763 class 440c fscm 81348

**End Connection Quantity:** 

3

**Regulation Type:** 

Automatic single stage

Valve Loading Method:

Spring

**Remote Actuation Method:** 

Piston

**Maximum Inlet Pressure Rating:** 

Not rated

## NSN 4820-00-842-2926

Fluid Pressure Regulating Valve - Page 2 of 2



Outlet Pressure Setting:
3000.0 pounds per square inch
Outlet Pressure Accuracy Rating:
Not rated
Filter:
Included
Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Reference Number Differentiating Characteristics:
As differentiated by source controlling dwg a51h9203 fscm 26512 $$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A21100