NSN 4820-00-844-8481

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-844-8481

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Pressure seal, ring type
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+4.0/+15.0 pounds per square inch
Maximum Operating Pressure:
50.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Opening Pressure Setting:
10.0 pounds per square inch
Material:
Copper alloy
Style Designator:
Err-090
Thread Series Designator:
Anpt 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-844-8481

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0