## NSN 4820-00-845-3580

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-845-3580

Pipe Size Accommodated:
2.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+0.0/+300.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
2.000 inches 1st end
Material:
Copper alloy
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Reference Number Differentiating Characteristics:
As differentiated by size of end connections
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-845-3580

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0