NSN 4820-00-845-4168

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-845-4168

0.250 inches 1st end						
Thread Direction:						
Right-hand 1st end						
Flow Control Device:						
Poppet						
Bonnet Type:						
Inside spring						
Bonnet Attachment Method:						
Integral						
Disk Loading Method:						
Spring						
Valve Discharge Flow Rate:						
504.0 pounds per hour						
Maximum Operating Temp:						
200.0 degrees fahrenheit single response						
Connection Style:						
G46b plain (pipe) 1st end						
Valve Operation Method:						
Automatic						
Connection Type:						
Threaded external pipe 1st end						
Features Provided:						
Valve stem lock shield and bonnet packing						
Thready Qty Per Inch (tpi):						
18 1st end						
Adjustable Pressure Range:						
+301.0/+350.0 pounds per square inch						
Maximum Operating Pressure:						
350.0 pounds per square inch single response						
Thread Size:						
0.250 inches 1st end						
Material:						
Steel seat						
Media For Which Designed:						
Steam single response						
Style Designator:						
Err-090						
Thread Series Designator:						
Nptf 1st end						
Shelf Life:						
N/a						

NSN 4820-00-845-4168

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0