## NSN 4820-00-848-7035

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-848-7035

**Body Material:** Aluminum alloy, qq-a-225/6, alloy 2024 **Outside Surface Treatment:** Anodized **Body Style:** Straight thru Media For Which Designed: Hydraulic fluid, mil-h-5606 **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 0.750-16 unjf **First End Thread Class:** 3b First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end **Seat Material:** Steel, federal standard 66, aisi/sae 1095 **Packing Material:** Rubber, synthetic, mil-p-25732 **Flow Control Device: Poppet** Flow Control Device Material: Steel, federal standard 66, aisi/sae 4130 **End Connection Quantity:** Renewable Seat Ring Type: Retaining ring **Regulation Type:** Automatic single stage Valve Loading Method: Spring **Remote Actuation Method:** Piston

**Maximum Inlet Pressure Rating:** 

1300.0 pounds per square inch

## NSN 4820-00-848-7035

Fluid Pressure Regulating Valve - Page 2 of 2



| Duliel Fressure Selling | Οι | utlet | <b>Pressure</b> | Setting |
|-------------------------|----|-------|-----------------|---------|
|-------------------------|----|-------|-----------------|---------|

1550.0 pounds per square inch

Filter:

Included

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A21100