NSN 4820-00-848-7876

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-848-7876

| Thread Class |
|---|
| Thread Class: 3a 1st end |
| Thread Direction: |
| |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 225.0 degrees fahrenheit single response |
| Connection Style: |
| Swivel nut, flared (tube) 2nd end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded external tube 2nd end |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 20 2nd end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.438 inches 2nd end |
| Outside Diameter Tube Accommodated: |
| 0.250 inches 2nd end |
| Material: |
| Steel comp 303 body |
| Material Specification: |
| 66 federal standard single material response body |
| Media For Which Designed: |
| Water-oil-gas single response |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| Tee |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-848-7876

Check Valve - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A530b0