NSN 4820-00-850-3024

Angle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-850-3024

| Pipe Size Accommodated: |
|--|
| 0.250 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Needle |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Maximum Operating Temp: |
| 500.0 degrees fahrenheit single response |
| Connection Style: |
| G9 plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 10000.0 pounds per square inch single response |
| Thread Size: |
| 0.250 inches 2nd end |
| Special Features: |
| The end connection identified above as the second end is the valve inlet |
| Material: |
| Steel seat |
| Material Specification: |
| Aisi416 assn standard single material response flow control device |
| Media For Which Designed: |
| Water-oil-gas single response |
| Surface Treatment: |
| Zinc |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-850-3024

Angle Valve - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A046b0