# NSN 4820-00-851-1848

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-851-1848

Thread Class:

3a 1st end

**Thread Direction:** 

Right-hand 1st end

## Flow Control Device:

Poppet

### **Disk Loading Method:**

Spring

#### **Connection Style:**

Flared (tube) 1st end

#### **Connection Type:**

Threaded external tube 1st end

#### **Mounting Position:**

Horizontal

#### Thready Qty Per Inch (tpi):

24 1st end

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### **Thread Size:**

0.375 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### **Outside Diameter Tube Accommodated:**

0.188 inches 1st end

#### **Special Features:**

2.110 in. Lg over-all, 0.625 in. Across flats

#### Material:

Steel flow control device

#### Media For Which Designed:

Air single response

#### Surface Treatment:

Enamel

### Style Designator:

Straight thru

# Test Data Document:

76301-32-72009 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Thread Series Designator:

Unf 1st end

## Shelf Life:

N/a

# Unit Of Measure:

# NSN 4820-00-851-1848

Restrictor Check Valve - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

