

View Online at <https://aerobasegroup.com/nsn/4820-00-851-4111>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Disk Loading Method:**

Weight

**Valve Discharge Flow Rate:**

12.0 gallons per minute

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

G42 flared (tube) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Features Provided:**

Pressure tight outlet side

**Thready Qty Per Inch (tpi):**

12 all ends

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.312 inches all ends

**Seat Angle:**

37.0 degrees all ends

**Opening Pressure Setting:**

80.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

1.000 inches 1st end

**Material:**

Stainless steel flow control device and rubber synthetic flow control device

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Err-090

**Thread Series Designator:**

Un all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.