## NSN 4820-00-852-4646

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-852-4646

## Thread Class:

3a all ends

**Thread Direction:** 

Right-hand all ends

## Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

450.0 degrees fahrenheit single response

#### **Connection Style:**

Flared (tube) all ends

#### Valve Operation Method:

Automatic

#### **Connection Type:**

#### Threaded external tube all ends

Mounting Position:

Horizontal

## Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### **Thread Size:**

0.562 inches all ends

#### Seat Angle:

37.0 degrees all ends

#### Material:

Stainless steel seat

## Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

#### Surface Treatment:

Passivate

#### Style Designator:

Straight thru

## Test Data Document:

99240-2c5100 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 4820-00-852-4646

Check Valve - Page 2 of 2

Fiig: A530b0

