NSN 4820-00-855-4143

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-855-4143

Pipe Size Accommodated:

0.500 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Cone

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield

Thready Qty Per Inch (tpi):

14 2nd end

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

0.500 inches 2nd end

Opening Pressure Setting:

15.0 pounds per square inch

Material:

Steel stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-855-4143

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

