NSN 4820-00-855-6818

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-855-6818

Pipe Size Accommodated:

0.500 inches 2nd end

Thread Class:

3a 1st end

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

24.6 pounds per hour

Maximum Operating Temp:

200.0 degrees fahrenheit single response

Connection Style:

G46b plain (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Maximum Operating Pressure:

450.0 pounds per square inch single response

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

300.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Material:

Copper alloy

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

NSN 4820-00-855-6818

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

