

View Online at <https://aerobasegroup.com/nsn/4820-00-859-8474>

Thread Class:

3b

End Connection Quantity:

3

End Application:

Applicable t.O. 9h8-14-243-3 fig 4

Current Rating In Amps:

0.6

Valve Operation Method:

Solenoid

Connection Type:

Threaded internal boss

Features Provided:

Continuous duty and normally closed

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

0.750 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Voltage In Volts And Current Type:

30.0 dc

Flow Pattern Quantity:

3

Spool Position Quantity:

2

Spool Quantity:

1

Special Features:

Manufacturers suggested name is valve assembly, solenoid pilot operated, 2 position, 3 way, normally-closed; media mil-h-5606; proof pressure 4500 psig; burst 7500 psig; voltage range 18 to 30 vdc; duty cycle continuous, ports 1/2 inch tube size per ms33649-8; temp range -65 to +160 degrees feh; wt 1.4 lbs; major component parts: solenoid assembly 1471-579146, spool & sleeve assembly h60g1081, body h60g1080; cure dated item repair parts kit h60g2243; major overhaul repair parts kit h60g2244; ports consists of pressure, return and cyl

Thread Series Designator:

Unjf

Furnished Items And Quantity:

1 pilot valve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A506h0