

View Online at <https://aerobasegroup.com/nsn/4820-00-859-8474>

**Thread Class:**

3b

**End Connection Quantity:**

3

**End Application:**

Applicable t.O. 9h8-14-243-3 fig 4

**Current Rating In Amps:**

0.6

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss

**Features Provided:**

Continuous duty and normally closed

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.750 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

160.0 degrees fahrenheit hydraulic fluid, petroleum base

**Voltage In Volts And Current Type:**

30.0 dc

**Flow Pattern Quantity:**

3

**Spool Position Quantity:**

2

**Spool Quantity:**

1

**Special Features:**

Manufacturers suggested name is valve assembly, solenoid pilot operated, 2 position, 3 way, normally-closed; media mil-h-5606; proof pressure 4500 psig; burst 7500 psig; voltage range 18 to 30 vdc; duty cycle continuous, ports 1/2 inch tube size per ms33649-8; temp range -65 to +160 degrees feh; wt 1.4 lbs; major component parts: solenoid assembly 1471-579146, spool & sleeve assembly h60g1081, body h60g1080; cure dated item repair parts kit h60g2243; major overhaul repair parts kit h60g2244; ports consists of pressure, return and cyl

**Thread Series Designator:**

Unjf

**Furnished Items And Quantity:**

1 pilot valve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

A506h0