

View Online at <https://aerobasegroup.com/nsn/4820-00-865-2170>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

0.5 cubic feet per minute

**Maximum Operating Temp:**

400.0 degrees fahrenheit single response

**Connection Style:**

G42 flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Valve stem lock shield and pressure tight outlet side

**Thready Qty Per Inch (tpi):**

20 1st end

**Maximum Operating Pressure:**

32.0 pounds per square inch single response

**Thread Size:**

0.437 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

25.0 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Stainless steel seat

**Media For Which Designed:**

Air single response

**Style Designator:**

Err-090

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0