NSN 4820-00-866-4618

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-866-4618

| Bonnet Type: |
|--|
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Renewable Seat Ring Type: |
| Threaded |
| Bolt Hole Quantity: |
| 8 1st end |
| Maximum Operating Temp: |
| 450.0 degrees fahrenheit 1st response |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Features Provided: |
| Bonnet packing |
| Valve Size: |
| 6.000 inches |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch 2nd response |
| Outside Diameter: |
| 11.000 inches all ends |
| Face To Face Distance: |
| 14.000 inches |
| Thickness: |
| 1.000 inches all ends |
| Bolt Hole Diameter: |
| 0.875 inches all ends |
| Bolt Circle Diameter: |
| 9.500 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Iron cast body |
| Material Specification: |
| Astmfea000 assn standard single material response body |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| |

NSN 4820-00-866-4618

Globe Valve - Page 2 of 2



| • |
|---|
| |

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0