Fluid Pressure Regulating Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-866-8151

Body Material:Aluminum alloyBody Style:TeeFurnished Items:Automatic relief valve and internal pilot valveFirst End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:Identical with first endSeat Material:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:1500.0 pounds per square inch	<b>-</b> • • • • •
Body Style:TeeTeeFurnished Items:Automatic relief valve and internal pilot valveFirst End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximun Inlet Pressure Rating:Suo0.0 pounds per square inchOutlet Pressure Setting:	-
TeeFurnished Items:Automatic relief valve and internal pilot valveFirst End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With First End:IdenticalSteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	-
Furnished Items:Automatic relief valve and internal pilot valveFirst End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:IdenticalSteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	Body Style:
Automatic relief valve and internal pilot valveFirst End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:IdenticalSeta Material:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	Тее
First End Connection Type:Threaded internal tubeFirst End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:IdenticalSetelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	Furnished Items:
Threaded internal tube First End Style Designator: Inverted flare First End Outside Diameter Tube Accommodated: 0.250 inches First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Setal Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Automatic relief valve and internal pilot valve
First End Style Designator:Inverted flareFirst End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:Identical with first endSetelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	First End Connection Type:
Inverted flare First End Outside Diameter Tube Accommodated: 0.250 inches First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Threaded internal tube
First End Outside Diameter Tube Accommodated:0.250 inchesFirst End Thread Size And Series/type Designator:7/16-20 unfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:Identical with first endSetelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	First End Style Designator:
0.250 inches First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Inverted flare
First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	First End Outside Diameter Tube Accommodated:
7/16-20 unf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	0.250 inches
First End Thread Direction:Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:Identical with first endSeat Material:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	First End Thread Size And Series/type Designator:
Right-handSecond End Relationship With First End:IdenticalThird End Relationship With Preceding Ends:Identical with first endSeat Material:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	7/16-20 unf
Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	First End Thread Direction:
Identical Third End Relationship With Preceding Ends: Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Right-hand
Third End Relationship With Preceding Ends:Identical with first endSeat Material:SteelEnd Connection Quantity:3Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	Second End Relationship With First End:
Identical with first end Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Identical
Seat Material: Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Third End Relationship With Preceding Ends:
Steel End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Identical with first end
End Connection Quantity: 3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Seat Material:
3 Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Steel
Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:3000.0 pounds per square inchOutlet Pressure Setting:	End Connection Quantity:
Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	3
Valve Loading Method: Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Regulation Type:
Spring Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Automatic single stage
Maximum Inlet Pressure Rating: 3000.0 pounds per square inch Outlet Pressure Setting:	Valve Loading Method:
3000.0 pounds per square inch Outlet Pressure Setting:	Spring
Outlet Pressure Setting:	Maximum Inlet Pressure Rating:
•	3000.0 pounds per square inch
1500.0 pounds per square inch	Outlet Pressure Setting:
	1500.0 pounds per square inch
Shelf Life:	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A21100	-