NSN 4820-00-867-2666

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-867-2666

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
470.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Width:
2.380 inches 2nd end
Length:
2.380 inches 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 2nd end
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
12 1st end
Maximum Operating Pressure:
85.0 pounds per square inch single response
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Bolt Hole Diameter:
0.281 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
1.810 inches 2nd end
Center To Center Distance Between Bolt Holes Along Width:
1.810 inches all ends
Flange Face Design:

Plain 2nd end

NSN 4820-00-867-2666

Check Valve - Page 2 of 2



Special Features:
W/drain port per ms33649-4
Material:
Aluminum alloy
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A530b0