

View Online at <https://aerobasegroup.com/nsn/4820-00-874-3750>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

Flared (tube) 2nd end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 2nd end

**Mounting Position:**

Horizontal

**Thready Qty Per Inch (tpi):**

20 2nd end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.438 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Outside Diameter Tube Accommodated:**

0.250 inches 2nd end

**Material:**

Stainless steel

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response

**Surface Treatment:**

Passivate

**Style Designator:**

Angle

**Test Data Document:**

99240-2c5842 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0