NSN 4820-00-877-4967

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-877-4967

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
12.0 degrees all ends
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Stainless steel
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:
Straight thru
Supplementary Features:
Flow control device: stem
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-00-877-4967

Restrictor Check Valve - Page 2 of 2



Fiig: A530b0

Mil-std (military Standard):

Mil-a-8625 spec.