NSN 4820-00-879-3574

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-879-3574

Pipe Size Accommodated:
0.750 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Valve stem lock shield and bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+40.0/+125.0 pounds per square inch
Maximum Operating Pressure:
125.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Opening Pressure Setting:
90.0 pounds per square inch
Material:
Steel
Material Specification:
Fed standard 66, aisi 304l/sae 30304l federal standard single material response
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

NSN 4820-00-879-3574

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0