# NSN 4820-00-879-3574

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-879-3574

## Pipe Size Accommodated:

0.750 inches all ends

## **Thread Direction:**

Right-hand all ends

### Flow Control Device:

Poppet

#### Bonnet Type:

Inside spring

#### **Bonnet Attachment Method:**

Integral

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

225.0 degrees fahrenheit single response

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded internal pipe all ends

## Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

## Adjustable Pressure Range:

+40.0/+125.0 pounds per square inch

#### Maximum Operating Pressure:

125.0 pounds per square inch single response

## Thread Size:

0.750 inches all ends

#### **Opening Pressure Setting:**

90.0 pounds per square inch

#### Material:

Steel

## **Material Specification:**

Fed standard 66, aisi 304l/sae 30304l federal standard single material response

## Media For Which Designed:

Air 1st response

# Style Designator:

Err-090

# Thread Series Designator:

Npt all ends

## Shelf Life:

N/a

# NSN 4820-00-879-3574

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

