## NSN 4820-00-882-1442

Safety Relief Valve - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/4820-00-882-1442

3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
15.0 gallons per minute
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
155.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 2nd end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
12 1st end
Adjustable Pressure Range:
+75.0/+1000.0 pounds per square inch
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
1.875 inches 1st end
Special Features:
W/handwheel to adjust relief pressure setting
Material:
Steel stem
Media For Which Designed:
Oil, hydraulic single response
Thread Series Designator:
Un 1st end

## NSN 4820-00-882-1442

Safety Relief Valve - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0