NSN 4820-00-882-5585

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-882-5585 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Minimum Operating Temp:** -65.0 degrees fahrenheit **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 20 2nd end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Seat Angle: 12.0 degrees all ends Material: Steel comp 303 flow control device **Material Specification:** Qq-s-764, type303-canceled federal specification single material response flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Straight thru **Thread Series Designator:** Unj all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-882-5585

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0