NSN 4820-00-882-7954

Globe Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Bolt Hole Quantity:

Bonnet Attachment Method:

Disk

U-bolt



View Online at https://aerobasegroup.com/nsn/4820-00-882-7954

8 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
7.500 inches 1st end
Thickness:
1.125 inches 1st end
Bolt Hole Diameter:
0.812 inches 1st end
Bolt Circle Diameter:
5.875 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
5.000 inches 1st end
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Specification Or Standard:
A composition
Departure From Cited Document:
In accordance with reply to pac ackm
Shelf Life:
N/a

NSN 4820-00-882-7954

Globe Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0