NSN 4820-00-887-4280

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-887-4280 **Body Material:** Aluminum alloy **Outside Surface Treatment:** Anodized, mil-a-8625, type 2 **Body Style:** Tee Media For Which Designed: Hydraulic fluid, phosphate-ester base **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 7/8&14 unf **First End Thread Class:** 3b First End Thread Direction: Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Not identical with first or second end **Third End Connection Type:** Threaded internal boss Third End Style Designator: Gasket seal Third End Thread Size And Series/type Designator: 3/4&16 unf **Third End Thread Class:** 3b **Third End Thread Direction:** Right-hand **Seat Material:** Steel, ams 5630 **Packing Material:** Rubber, synthetic Flow Control Device: **Poppet**

Steel, ams 5630

End Connection Quantity:

Flow Control Device Material:

NSN 4820-00-887-4280

Fluid Pressure Regulating Valve - Page 2 of 2



| Renewable Seat Ring Type: |
|---|
| Pressed-in |
| Outlet Pressure Range: |
| +90.0/+105.0 pounds per square inch |
| Regulation Type: |
| Automatic double stage |
| Valve Loading Method: |
| Spring |
| Maximum Inlet Pressure Rating: |
| 3000.0 pounds per square inch |
| Filter: |
| Not included |
| Геmpurature Rating: |
| Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A21100 |
| |