

View Online at <https://aerobasegroup.com/nsn/4820-00-887-4280>

**Body Material:**

Aluminum alloy

**Outside Surface Treatment:**

Anodized, mil-a-8625, type 2

**Body Style:**

Tee

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base

**First End Connection Type:**

Threaded internal boss

**First End Style Designator:**

Gasket seal

**First End Thread Size And Series/type Designator:**

7/8&14 unf

**First End Thread Class:**

3b

**First End Thread Direction:**

Right-hand

**Second End Relationship With First End:**

Identical

**Third End Relationship With Preceding Ends:**

Not identical with first or second end

**Third End Connection Type:**

Threaded internal boss

**Third End Style Designator:**

Gasket seal

**Third End Thread Size And Series/type Designator:**

3/4&16 unf

**Third End Thread Class:**

3b

**Third End Thread Direction:**

Right-hand

**Seat Material:**

Steel, ams 5630

**Packing Material:**

Rubber, synthetic

**Flow Control Device:**

Poppet

**Flow Control Device Material:**

Steel, ams 5630

**End Connection Quantity:**

3

**Renewable Seat Ring Type:**

Pressed-in

**Outlet Pressure Range:**

+90.0/+105.0 pounds per square inch

**Regulation Type:**

Automatic double stage

**Valve Loading Method:**

Spring

**Maximum Inlet Pressure Rating:**

3000.0 pounds per square inch

**Filter:**

Not included

**Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A21100