NSN 4820-00-889-2425

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-889-2425

Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
31000.0 pounds per hour
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Valve stem lock shield
Adjustable Pressure Range:
+696.0/+760.0 pounds per square inch
Maximum Operating Pressure:
900.0 pounds per square inch single response
Opening Pressure Setting:
700.0 pounds per square inch
Outside Diameter:
9.000 inches 2nd end
Thickness:
1.125 inches 1st end
Bolt Hole Diameter:
0.875 inches 2nd end
Bolt Circle Diameter:
7.250 inches 2nd end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.688 inches 1st end
Raised Face Diameter:
5.000 inches 1st end
Material:
Stainless steel seat
Style Designator:

Err-090

NSN 4820-00-889-2425

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0