## NSN 4820-00-889-2426

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-889-2426 Flow Control Device: Poppet **Bonnet Type:** Packing retaining **Disk Loading Method:** Spring Valve Discharge Flow Rate: 43000.0 pounds per hour **Bolt Hole Quantity:** 8 2nd end **Valve Operation Method:** Automatic Flange Shape: Round with holes 2nd end **Connection Type:** Flange 1st end **Features Provided:** Valve stem lock shield Adjustable Pressure Range: +672.0/+732.0 pounds per square inch **Opening Pressure Setting:** 700.0 pounds per square inch **Outside Diameter:** 9.000 inches 2nd end Thickness: 1.125 inches 2nd end **Bolt Hole Diameter:** 0.875 inches 2nd end **Bolt Circle Diameter:** 7.250 inches 2nd end Flange Face Design: Raised straight 2nd end **Raised Face Height:** 0.750 inches 1st end **Raised Face Diameter:** 5.000 inches 1st end Material: Steel body Style Designator: Err-090

N/a

Shelf Life:

## NSN 4820-00-889-2426

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0