# NSN 4820-00-891-0987

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-891-0987

Pipe Size Accommodated:

0.375 inches all ends

**Thread Direction:** 

Right-hand all ends

### Flow Control Device:

Disk

#### Bonnet Type:

Inside spring

#### **Bonnet Attachment Method:**

Threaded

### **Disk Loading Method:**

Spring

#### Valve Discharge Flow Rate:

25.0 gallons per minute

#### **Connection Style:**

G9 plain, optional en (pipe) all ends

#### Valve Operation Method:

Automatic

### **Connection Type:**

Threaded internal pipe all ends

### Mounting Facility:

Bulkhead

## **Features Provided:**

Bonnet packing and pressure tight outlet side

#### Adjustable Pressure Range:

+0.0/+350.0 pounds per square inch

#### Maximum Operating Pressure:

300.0 pounds per square inch single response

#### Thread Size:

0.375 inches all ends

#### Material:

Steel stem

#### Media For Which Designed:

Hydraulic fluid, mineral base single response

#### Surface Treatment:

Oxide and paint

#### Style Designator:

Err-090

### **Thread Series Designator:**

Nptf all ends

## Furnished Items And Quantity:

1 bolt and 1 nut

# NSN 4820-00-891-0987

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

