# NSN 4820-00-891-3343

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-891-3343

Thread Class:	
3b 2nd end	

Thread Direction:

Right-hand 1st end

## Flow Control Device:

Poppet

### **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

275.0 degrees fahrenheit single response

**Connection Style:** 

Gasket seal (boss) 2nd end

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded internal boss 2nd end

**Mounting Position:** 

Horizontal or vertical

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

### Thread Size:

0.438 inches 2nd end

#### Seat Angle:

37.0 degrees 1st end

Material:

Rubber synthetic packing

#### **Material Specification:**

Qq-a-225/6, alloy 2024 federal specification single material response body

#### Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

## Style Designator:

Straight thru

# **Thread Series Designator:**

Unf 2nd end

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 4820-00-891-3343

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.