

View Online at <https://aerobasegroup.com/nsn/4820-00-892-2127>

Flow Control Device:

Needle

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

800.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

0.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

3.375 inches all ends

Thickness:

0.438 inches all ends

First Connection Face To Centerline Distance:

3.188 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

3.188 inches

Bolt Circle Diameter:

2.250 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

1.250 inches all ends

Material:

Steel stem

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Specification Or Standard:

B composition and 600 rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0