NSN 4820-00-896-4196

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-896-4196

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
7.0 gallons per minute
End Application:
N/h/a p/n 3h10305-101 c-141 acft
Connection Style:
G4 gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+825.0/+1400.0 pounds per square inch
Maximum Operating Pressure:
1400.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Opening Pressure Setting:
1200.0 pounds per square inch
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Err-090
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-896-4196

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0