NSN 4820-00-896-4667

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-896-4667 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Piston **Disk Loading Method:** Spring **Maximum Operating Temp:** 50.0 degrees celsius single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Features Provided:** Pressure tight outlet side **Power Drive Operating Pressure:** 10.0 pounds per square inch **Adjustable Pressure Range:** +10.0/+80.0 pounds per square inch **Maximum Operating Pressure:** 80.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 10.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Stainless steel body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment: Passivate Style Designator:**

Thread Series Designator: Unf 2nd end

Shelf Life:

Err-090

N/a

NSN 4820-00-896-4667

Safety Relief Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0