## NSN 4820-00-896-4667

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-896-4667

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Piston
Disk Loading Method:
Spring
Maximum Operating Temp:
50.0 degrees celsius single response
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 2nd end
Features Provided:
Pressure tight outlet side
Power Drive Operating Pressure:
10.0 pounds per square inch
Adjustable Pressure Range:
+10.0/+80.0 pounds per square inch
Maximum Operating Pressure:
80.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
10.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Material:
Stainless steel body
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Style Designator:
Err-090
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

## NSN 4820-00-896-4667

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

