NSN 4820-00-899-0163

Globe Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-899-0163

Plug
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
500.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Valve Size:
2.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
7.000 inches 1st end
Face To Face Distance:
11.625 inches
Thickness:
0.625 inches 1st end
Bolt Hole Diameter:
0.688 inches 1st end
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
4.125 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:

Steam single response

NSN 4820-00-899-0163

Globe Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0