## NSN 4820-00-900-9928

Restrictor Check Valve - Page 1 of 2



Restrictor Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-900-9928
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Unable To Decode:
Unable to decode and unable to decode
Flow Control Device:
Cone
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit 2nd response
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.875 inches all ends
Seat Angle:
37.0 degrees all ends
Special Features:
Item to be stamped w/buord dwg no.2049913 and rev no.In lieu of part no.
Material:
Stainless steel flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Straight thru
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4820-00-900-9928

Restrictor Check Valve - Page 2 of 2

Fiig: A530b0

