NSN 4820-00-903-3753

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-903-3753

Thread Class: 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Poppet **Disk Loading Method:** Spring Valve Discharge Flow Rate: 2.5 gallons per minute Maximum Operating Temp: 275.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends Valve Operation Method: Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Adjustable Pressure Range: +1400.0/+2300.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Material: Steel flow control device Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Style Designator: Err-090 **Test Data Document:** 81349-mil-v-8813 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf all ends Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-903-3753

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

