

View Online at <https://aerobasegroup.com/nsn/4820-00-903-4331>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Valve Operation Method:

Manual

Flange Shape:

Round 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

300.0 pounds per square inch single response

Criticality Code Justification:

Zzzy

Outside Diameter:

6.125 inches 1st end

Thickness:

0.813 inches 1st end

First Connection Face To Centerline Distance:

4.500 inches

Second Connection Face To Centerline Distance:

4.500 inches

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.063 inches 1st end

Raised Face Diameter:

2.875 inches 1st end

Material:

Steel comp 316l seat

Style Designator:

Err-090

Test Data Document:

96169-2620-925x3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Or Standard:

Rd assembly

Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0